



SCL K07-TS-MOR																							
		2000			2250			2500			2750			2900			3250			3500			
Pressure	dp [mbar]	dp [inWG]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]
	325	130	-	-	-	-	-	-	-	-	-	-	-	-	182	12.48	15.00	-	-	-	-	-	-
	300	120	-	-	-	-	-	-	-	-	-	165	10.88	15.00	206	11.69	15.00	295	13.71	15.00	-	-	-
	275	110	-	-	-	-	-	-	-	-	-	190	10.12	15.00	229	10.89	15.00	316	12.82	15.00	-	-	-
	250	100	-	-	-	-	-	-	148	8.23	15.00	215	9.37	15.00	253	10.10	15.00	336	11.93	15.00	393	13.37	15.00
	225	90	-	-	-	-	-	-	175	7.54	15.00	239	8.62	15.00	276	9.30	10.00	357	11.04	15.00	413	12.41	15.00
	200	80	-	-	-	136	5.94	15.00	202	6.86	10.00	264	7.86	10.00	299	8.51	10.00	378	10.15	15.00	432	11.45	15.00
	175	70	-	-	-	166	5.32	10.00	229	6.17	10.00	289	7.11	10.00	323	7.71	10.00	399	9.26	10.00	452	10.49	15.00
	150	60	132	3.99	10.00	197	4.70	10.00	257	5.49	10.00	313	6.35	7.50	346	6.92	7.50	420	8.37	10.00	471	9.53	15.00
	125	50	166	3.45	10.00	227	4.09	7.50	284	4.80	7.50	338	5.60	7.50	370	6.12	7.50	441	7.48	10.00	490	8.57	10.00
	100	40	200	2.90	7.50	257	3.47	7.50	311	4.12	7.50	363	4.85	7.50	393	5.33	7.50	462	6.59	7.50	510	7.61	10.00
	75	30	234	2.35	7.50	287	2.85	7.50	338	3.43	7.50	387	4.09	7.50	416	4.53	7.50	483	5.70	7.50	529	6.65	7.50
	50	20	268	1.80	7.50	317	2.24	7.50	365	2.75	7.50	412	3.34	7.50	440	3.74	7.50	504	4.81	7.50	549	5.70	7.50
	25	10	302	1.25	7.50	347	1.62	7.50	392	2.06	7.50	437	2.59	7.50	463	2.94	7.50	525	3.91	7.50	568	4.74	7.50
0	0	336	0.70	7.50	378	1.00	7.50	420	1.38	7.50	462	1.83	7.50	487	2.15	7.50	545	3.02	7.50	587	3.78	7.50	

Curves refer to air at 68°F temperature and 29.92 In Hg atmospheric pressure (abs) measured at inlet port.  
 Values for flow and power consumption: +/-10% tolerance.  
 Data subject to change without notice.