



SCL K07-TS-MOR																								
		2000			2250			2500			2750			2900			3250			3500				
Vacuum	dp	dp	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	
	[mbar]	[inWG]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	
	275	110	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	298	14.33	15.00
	250	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	330	13.37	15.00
	225	90	-	-	-	-	-	-	-	-	-	-	-	-	216	9.30	10.00	316	11.04	15.00	363	12.41	15.00	
	200	80	-	-	-	-	-	-	-	-	-	209	7.86	10.00	253	8.51	10.00	347	10.15	15.00	393	11.45	15.00	
	175	70	-	-	-	-	-	-	173	6.17	10.00	247	7.11	10.00	288	7.71	10.00	375	9.26	10.00	423	10.49	15.00	
	150	60	-	-	-	139	4.70	10.00	216	5.49	10.00	284	6.35	7.50	321	6.92	7.50	403	8.37	10.00	450	9.53	15.00	
	125	50	109	3.45	10.00	188	4.09	7.50	256	4.80	7.50	318	5.60	7.50	353	6.12	7.50	430	7.48	10.00	477	8.57	10.00	
	100	40	164	2.90	7.50	233	3.47	7.50	294	4.12	7.50	351	4.85	7.50	383	5.33	7.50	455	6.59	7.50	502	7.61	10.00	
	75	30	215	2.35	7.50	274	2.85	7.50	329	3.43	7.50	381	4.09	7.50	411	4.53	7.50	479	5.70	7.50	525	6.65	7.50	
	50	20	260	1.80	7.50	312	2.24	7.50	362	2.75	7.50	410	3.34	7.50	438	3.74	7.50	502	4.81	7.50	547	5.70	7.50	
25	10	300	1.25	7.50	346	1.62	7.50	392	2.06	7.50	436	2.59	7.50	463	2.94	7.50	524	3.91	7.50	568	4.74	7.50		
0	0	335	0.70	7.50	377	1.00	7.50	419	1.38	7.50	461	1.83	7.50	486	2.15	7.50	545	3.02	7.50	587	3.78	7.50		

Curves refer to air at 68°F temperature, measured at inlet port and 29.92 In Hg atmospheric backpressure (abs)
 Values for flow and power consumption: +/-10% tolerance.
 Data subject to change without notice.