



SCL K08-TS-MOR																								
		2000			2250			2500			2750			2900			3250			3500				
Vacuum	dp	dp	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	
	[mbar]	[inWG]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	
	225	90	-	-	-	-	-	-	-	-	-	-	-	-	-	386	14.00	15.00	-	-	-	-	-	-
	200	80	-	-	-	-	-	-	-	-	-	369	11.83	15.00	409	12.76	15.00	-	-	-	-	-	-	
	175	70	-	-	-	-	-	-	325	9.30	15.00	393	10.66	15.00	432	11.53	15.00	521	13.74	15.00	-	-	-	
	150	60	-	-	-	282	7.10	15.00	351	8.24	15.00	417	9.48	15.00	455	10.29	15.00	541	12.36	15.00	601	14.00	15.00	
	125	50	242	5.21	15.00	312	6.14	15.00	378	7.17	15.00	441	8.31	15.00	478	9.05	15.00	562	10.97	15.00	620	12.51	15.00	
	100	40	276	4.35	15.00	342	5.18	15.00	404	6.10	15.00	465	7.14	15.00	501	7.82	15.00	582	9.58	15.00	639	11.02	15.00	
	75	30	309	3.50	15.00	371	4.22	15.00	431	5.04	15.00	489	5.97	15.00	524	6.58	15.00	602	8.20	15.00	658	9.52	15.00	
	50	20	342	2.65	15.00	401	3.26	15.00	458	3.97	15.00	513	4.79	15.00	546	5.34	15.00	623	6.81	15.00	677	8.03	15.00	
25	10	375	1.79	15.00	430	2.30	15.00	484	2.90	15.00	537	3.62	15.00	569	4.11	15.00	643	5.43	15.00	696	6.54	15.00		
0	0	408	0.94	15.00	459	1.34	15.00	510	1.84	15.00	561	2.45	15.00	592	2.87	15.00	663	4.04	15.00	715	5.05	15.00		

Curves refer to air at 68°F temperature, measured at inlet port and 29.92 In Hg atmospheric backpressure (abs)
 Values for flow and power consumption: +/-10% tolerance.
 Data subject to change without notice.