



SCL K09 MS-MOR																													
		2000			2250			2500			2750			2900			3250			3500			3750			4000			
Vacuum	dp	dp	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.
	[mbar]	[inWG]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]
	325	130	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	260	13.20	15.00	-	-	-	-	-	-
	300	120	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	281	12.43	15.00	334	13.84	15.00	-	-	-
	275	110	-	-	-	-	-	-	-	-	-	-	-	-	184	8.83	10.00	265	10.43	15.00	301	11.67	15.00	352	13.02	15.00	-	-	-
	250	100	-	-	-	-	-	-	-	-	-	171	7.60	10.00	208	8.20	10.00	284	9.71	15.00	321	10.90	15.00	369	12.20	15.00	415	13.60	15.00
	225	90	-	-	-	-	-	-	-	-	-	197	6.99	10.00	231	7.56	10.00	303	9.00	10.00	340	10.14	15.00	386	11.38	15.00	430	12.72	15.00
	200	80	-	-	-	-	-	-	163	5.56	10.00	221	6.39	7.50	253	6.93	7.50	321	8.29	10.00	357	9.37	10.00	402	10.56	15.00	444	11.85	15.00
	175	70	-	-	-	130	4.31	10.00	191	5.01	7.50	244	5.79	7.50	274	6.29	7.50	338	7.58	10.00	374	8.61	10.00	417	9.74	15.00	458	10.97	15.00
	150	60	98	3.23	7.50	162	3.82	7.50	217	4.47	7.50	266	5.19	7.50	294	5.65	7.50	355	6.86	7.50	391	7.84	10.00	431	8.91	10.00	471	10.09	15.00
	125	50	135	2.80	7.50	191	3.33	7.50	241	3.92	7.50	286	4.58	7.50	312	5.02	7.50	370	6.15	7.50	406	7.07	7.50	445	8.09	10.00	483	9.22	10.00
	100	40	168	2.36	7.50	218	2.83	7.50	263	3.37	7.50	306	3.98	7.50	330	4.38	7.50	385	5.44	7.50	421	6.31	7.50	458	7.27	10.00	495	8.34	10.00
	75	30	198	1.92	7.50	243	2.34	7.50	284	2.82	7.50	323	3.38	7.50	346	3.75	7.50	399	4.73	7.50	434	5.54	7.50	471	6.45	7.50	507	7.46	10.00
	50	20	225	1.48	7.50	265	1.85	7.50	303	2.27	7.50	340	2.77	7.50	362	3.11	7.50	412	4.01	7.50	447	4.77	7.50	482	5.63	7.50	518	6.59	7.50
	25	10	248	1.04	7.50	285	1.35	7.50	320	1.73	7.50	355	2.17	7.50	376	2.48	7.50	425	3.30	7.50	459	4.00	7.50	494	4.80	7.50	528	5.71	7.50
	0	0	268	0.60	7.50	302	0.86	7.50	336	1.18	7.50	369	1.57	7.50	389	1.84	7.50	436	2.59	7.50	470	3.24	7.50	504	3.98	7.50	538	4.83	7.50

Curves refer to air at 68°F temperature, measured at inlet port and 29.92 In Hg atmospheric backpressure (abs)
 Values for flow and power consumption: +/-10% tolerance.
 Data subject to change without notice.