



SCL K11-TD-MOR																						
		2000			2250			2500			2750			2900			3250			3500		
dp [mbar]	dp [inWG]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]
425	170	-	-	-	-	-	-	-	-	-	-	-	-	333	20.80	25.00	-	-	-	-	-	-
400	160	-	-	-	-	-	-	-	-	-	-	-	-	350	19.89	25.00	-	-	-	-	-	-
375	150	-	-	-	-	-	-	-	-	-	321	17.49	25.00	367	18.98	25.00	464	22.81	25.00	-	-	-
350	140	-	-	-	-	-	-	258	14.40	25.00	339	16.63	25.00	383	18.07	25.00	476	21.79	25.00	-	-	-
325	130	-	-	-	-	-	-	279	13.61	25.00	356	15.76	25.00	398	17.16	25.00	488	20.77	25.00	546	23.66	25.00
300	120	-	-	-	215	10.96	25.00	300	12.83	25.00	373	14.90	25.00	413	16.25	25.00	499	19.75	25.00	556	22.57	25.00
275	110	-	-	-	240	10.25	25.00	319	12.04	25.00	388	14.04	25.00	427	15.35	25.00	510	18.73	25.00	565	21.47	25.00
250	100	176	8.02	25.00	264	9.55	25.00	337	11.26	25.00	403	13.18	25.00	440	14.44	25.00	520	17.71	25.00	574	20.37	25.00
225	90	205	7.40	25.00	285	8.84	25.00	355	10.48	25.00	417	12.32	25.00	452	13.53	25.00	530	16.69	25.00	582	19.27	25.00
200	80	232	6.77	25.00	306	8.14	25.00	370	9.69	25.00	430	11.46	25.00	463	12.62	25.00	539	15.68	25.00	590	18.18	25.00
175	70	256	6.14	25.00	324	7.43	25.00	385	8.91	25.00	442	10.59	25.00	474	11.71	25.00	547	14.66	25.00	598	17.08	25.00
150	60	279	5.52	25.00	341	6.73	25.00	399	8.13	25.00	453	9.73	25.00	484	10.80	25.00	555	13.64	25.00	605	15.98	25.00
125	50	299	4.89	25.00	357	6.02	25.00	411	7.34	25.00	463	8.87	25.00	494	9.89	25.00	563	12.62	25.00	612	14.89	25.00
100	40	316	4.26	25.00	371	5.32	25.00	423	6.56	25.00	473	8.01	25.00	502	8.98	25.00	570	11.60	25.00	618	13.79	25.00
75	30	332	3.63	25.00	383	4.61	25.00	433	5.78	25.00	481	7.15	25.00	510	8.07	25.00	577	10.58	25.00	624	12.69	25.00
50	20	345	3.01	25.00	394	3.91	25.00	442	4.99	25.00	489	6.28	25.00	517	7.17	25.00	583	9.56	25.00	629	11.60	25.00
25	10	356	2.38	25.00	403	3.20	25.00	450	4.21	25.00	496	5.42	25.00	524	6.26	25.00	588	8.55	25.00	634	10.50	25.00
0	0	365	1.75	25.00	411	2.50	25.00	456	3.43	25.00	502	4.56	25.00	529	5.35	25.00	593	7.53	25.00	639	9.40	25.00

Curves refer to air at 68°F temperature and 29.92 In Hg atmospheric pressure (abs) measured at inlet port.
 Values for flow and power consumption: +/-10% tolerance.
 Data subject to change without notice.