



SCL K11-TS-MOR																								
		2000			2250			2500			2750			2900			3250			3500				
Pressure	dp [mbar]	dp [inWG]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	
	275	110	-	-	-	-	-	-	-	-	-	-	-	-	-	708	26.90	30.00	-	-	-	-	-	-
	250	100	-	-	-	-	-	-	-	-	-	668	23.12	30.00	738	25.15	30.00	-	-	-	-	-	-	
	225	90	-	-	-	-	-	-	581	18.48	30.00	700	21.46	30.00	768	23.40	25.00	923	28.42	30.00	-	-	-	
	200	80	-	-	-	496	14.44	30.00	616	16.97	25.00	731	19.80	25.00	798	21.65	25.00	949	26.46	30.00	-	-	-	
	175	70	-	-	-	535	13.08	25.00	651	15.46	25.00	763	18.14	25.00	828	19.90	25.00	976	24.50	30.00	1079	28.24	30.00	
	150	60	455	9.75	25.00	573	11.72	25.00	686	13.96	25.00	795	16.48	25.00	858	18.15	25.00	1003	22.54	25.00	1104	26.13	30.00	
	125	50	498	8.54	25.00	612	10.36	25.00	721	12.45	25.00	826	14.82	25.00	888	16.40	25.00	1030	20.58	25.00	1129	24.02	30.00	
	100	40	542	7.34	25.00	651	9.01	25.00	756	10.94	25.00	858	13.16	25.00	918	14.65	25.00	1057	18.62	25.00	1154	21.90	25.00	
	75	30	586	6.13	25.00	690	7.65	25.00	791	9.43	25.00	890	11.51	25.00	948	12.90	25.00	1083	16.66	25.00	1179	19.79	25.00	
	50	20	629	4.92	25.00	728	6.29	25.00	825	7.92	25.00	921	9.85	25.00	978	11.15	25.00	1110	14.70	25.00	1203	17.68	25.00	
	25	10	673	3.72	25.00	767	4.93	25.00	860	6.41	25.00	953	8.19	25.00	1008	9.40	25.00	1137	12.74	25.00	1228	15.57	25.00	
	0	0	716	2.51	25.00	806	3.58	25.00	895	4.90	25.00	985	6.53	25.00	1038	7.65	25.00	1164	10.77	25.00	1253	13.46	25.00	

Curves refer to air at 68°F temperature and 29.92 In Hg atmospheric pressure (abs) measured at inlet port.  
 Values for flow and power consumption: +/-10% tolerance.  
 Data subject to change without notice.