



SCL K11-TS-MOR																								
		2000			2250			2500			2750			2900			3250			3500				
Vacuum	dp	dp	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	Q	Pow	E.M.	
	[mbar]	[inWG]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	[cfm]	[hp]	[hp]	
	275	110	-	-	-	-	-	-	-	-	-	-	-	-	-	592	26.90	30.00	-	-	-	-	-	-
	250	100	-	-	-	-	-	-	-	-	-	555	23.12	30.00	643	25.15	30.00	-	-	-	-	-	-	
	225	90	-	-	-	-	-	-	459	18.48	30.00	609	21.46	30.00	692	23.40	25.00	870	28.42	30.00	-	-	-	
	200	80	-	-	-	362	14.44	30.00	521	16.97	25.00	661	19.80	25.00	739	21.65	25.00	909	26.46	30.00	-	-	-	
	175	70	-	-	-	434	13.08	25.00	579	15.46	25.00	710	18.14	25.00	784	19.90	25.00	946	24.50	30.00	1055	28.24	30.00	
	150	60	348	9.75	25.00	500	11.72	25.00	634	13.96	25.00	756	16.48	25.00	826	18.15	25.00	981	22.54	25.00	1087	26.13	30.00	
	125	50	426	8.54	25.00	562	10.36	25.00	686	12.45	25.00	801	14.82	25.00	867	16.40	25.00	1015	20.58	25.00	1118	24.02	30.00	
	100	40	496	7.34	25.00	620	9.01	25.00	734	10.94	25.00	842	13.16	25.00	905	14.65	25.00	1048	18.62	25.00	1147	21.90	25.00	
	75	30	561	6.13	25.00	673	7.65	25.00	779	9.43	25.00	881	11.51	25.00	941	12.90	25.00	1079	16.66	25.00	1175	19.79	25.00	
	50	20	619	4.92	25.00	722	6.29	25.00	821	7.92	25.00	918	9.85	25.00	976	11.15	25.00	1108	14.70	25.00	1202	17.68	25.00	
25	10	671	3.72	25.00	766	4.93	25.00	859	6.41	25.00	952	8.19	25.00	1008	9.40	25.00	1136	12.74	25.00	1228	15.57	25.00		
0	0	716	2.51	25.00	805	3.58	25.00	895	4.90	25.00	984	6.53	25.00	1038	7.65	25.00	1163	10.77	25.00	1253	13.46	25.00		

Curves refer to air at 68°F temperature, measured at inlet port and 29.92 In Hg atmospheric backpressure (abs)  
 Values for flow and power consumption: +/-10% tolerance.  
 Data subject to change without notice.