



SCL K12-TD-MOR																								
		2000			2250			2500			2750			2900			3250			3500				
Pressure	dp [mbar]	dp [inWG]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	
	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	425	170	-	-	-	-	-	-	-	-	-	-	-	-	481	28.50	30.00	-	-	-	-	-	-	-
	400	160	-	-	-	-	-	-	-	-	-	-	-	-	488	27.27	30.00	-	-	-	-	-	-	-
	375	150	-	-	-	-	-	-	-	-	-	458	23.97	30.00	494	26.04	30.00	-	-	-	-	-	-	-
	350	140	-	-	-	-	-	-	404	19.71	30.00	465	22.80	30.00	501	24.81	30.00	-	-	-	-	-	-	-
	325	130	-	-	-	-	-	-	412	18.65	30.00	472	21.64	30.00	507	23.58	25.00	-	-	-	-	-	-	-
	300	120	-	-	-	358	15.00	30.00	419	17.59	25.00	479	20.47	25.00	514	22.35	25.00	594	27.23	30.00	-	-	-	-
	275	110	-	-	-	366	14.04	25.00	427	16.53	25.00	486	19.30	25.00	521	21.12	25.00	600	25.85	30.00	-	-	-	-
	250	100	313	10.97	25.00	375	13.09	25.00	435	15.47	25.00	493	18.14	25.00	527	19.89	25.00	606	24.47	30.00	661	28.20	30.00	-
	225	90	323	10.12	25.00	384	12.13	25.00	443	14.41	25.00	500	16.97	25.00	534	18.66	25.00	612	23.10	25.00	667	26.71	30.00	-
	200	80	332	9.28	25.00	392	11.18	25.00	450	13.35	25.00	507	15.81	25.00	540	17.44	25.00	618	21.72	25.00	672	25.23	30.00	-
	175	70	342	8.43	25.00	401	10.23	25.00	458	12.29	25.00	514	14.64	25.00	547	16.21	25.00	624	20.34	25.00	678	23.75	25.00	-
	150	60	352	7.58	25.00	409	9.27	25.00	465	11.23	25.00	521	13.48	25.00	554	14.98	25.00	629	18.96	25.00	683	22.26	25.00	-
	125	50	361	6.73	25.00	418	8.32	25.00	473	10.17	25.00	528	12.31	25.00	560	13.75	25.00	635	17.59	25.00	688	20.78	25.00	-
	100	40	371	5.88	25.00	426	7.36	25.00	481	9.11	25.00	535	11.14	25.00	567	12.52	25.00	641	16.21	25.00	694	19.30	25.00	-
	75	30	380	5.04	25.00	435	6.41	25.00	488	8.05	25.00	541	9.98	25.00	573	11.29	25.00	647	14.83	25.00	699	17.81	25.00	-
	50	20	390	4.19	25.00	443	5.46	25.00	496	6.99	25.00	548	8.81	25.00	580	10.06	25.00	653	13.45	25.00	705	16.33	25.00	-
	25	10	399	3.34	25.00	452	4.50	25.00	503	5.93	25.00	555	7.65	25.00	586	8.83	25.00	659	12.07	25.00	710	14.84	25.00	-
	0	0	409	2.49	25.00	460	3.55	25.00	511	4.87	25.00	562	6.48	25.00	593	7.60	25.00	664	10.70	25.00	715	13.36	25.00	-

Curves refer to air at 68°F temperature, measured at inlet port and 29.92 In Hg atmospheric backpressure (abs)
 Values for flow and power consumption: +/-10% tolerance.
 Data subject to change without notice.