



| SCL K12-TD-MOR | | | | | | | | | | | | | | | | | | | | | | |
|----------------|--------|-------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | | 2000 | | | 2250 | | | 2500 | | | 2750 | | | 2900 | | | 3250 | | | 3500 | | |
| dp | dp | Q | Pow | E.M. | Q | Pow | E.M. | Q | Pow | E.M. | Q | Pow | E.M. | Q | Pow | E.M. | Q | Pow | E.M. | Q | Pow | E.M. |
| [mbar] | [inWG] | [cfm] | [hp] | [hp] | [cfm] | [hp] | [hp] | [cfm] | [hp] | [hp] | [cfm] | [hp] | [hp] | [cfm] | [hp] | [hp] | [cfm] | [hp] | [hp] | [cfm] | [hp] | [hp] |
| 425 | 170 | - | - | - | - | - | - | - | - | - | - | - | - | 412 | 25.33 | 30.00 | - | - | - | - | - | - |
| 400 | 160 | - | - | - | - | - | - | - | - | - | - | - | - | 427 | 24.29 | 30.00 | - | - | - | - | - | - |
| 375 | 150 | - | - | - | - | - | - | - | - | - | 395 | 21.32 | 25.00 | 441 | 23.25 | 25.00 | 540 | 28.23 | 30.00 | - | - | - |
| 350 | 140 | - | - | - | - | - | - | - | - | - | 411 | 20.33 | 25.00 | 455 | 22.20 | 25.00 | 551 | 27.06 | 30.00 | - | - | - |
| 325 | 130 | - | - | - | - | - | - | 348 | 16.56 | 25.00 | 426 | 19.34 | 25.00 | 469 | 21.16 | 25.00 | 562 | 25.89 | 30.00 | - | - | - |
| 300 | 120 | - | - | - | - | - | - | 366 | 15.66 | 25.00 | 440 | 18.35 | 25.00 | 481 | 20.11 | 25.00 | 572 | 24.71 | 30.00 | 633 | 28.45 | 30.00 |
| 275 | 110 | - | - | - | 304 | 12.45 | 25.00 | 383 | 14.76 | 25.00 | 454 | 17.36 | 25.00 | 494 | 19.07 | 25.00 | 582 | 23.54 | 25.00 | 642 | 27.19 | 30.00 |
| 250 | 100 | - | - | - | 324 | 11.64 | 25.00 | 399 | 13.86 | 25.00 | 467 | 16.37 | 25.00 | 505 | 18.02 | 25.00 | 591 | 22.37 | 25.00 | 650 | 25.93 | 30.00 |
| 225 | 90 | 263 | 8.97 | 25.00 | 343 | 10.83 | 25.00 | 414 | 12.96 | 25.00 | 479 | 15.38 | 25.00 | 517 | 16.98 | 25.00 | 600 | 21.20 | 25.00 | 658 | 24.67 | 30.00 |
| 200 | 80 | 286 | 8.25 | 25.00 | 361 | 10.02 | 25.00 | 428 | 12.06 | 25.00 | 491 | 14.39 | 25.00 | 527 | 15.94 | 25.00 | 609 | 20.03 | 25.00 | 665 | 23.41 | 25.00 |
| 175 | 70 | 307 | 7.53 | 25.00 | 377 | 9.21 | 25.00 | 441 | 11.16 | 25.00 | 502 | 13.40 | 25.00 | 537 | 14.89 | 25.00 | 617 | 18.86 | 25.00 | 673 | 22.15 | 25.00 |
| 150 | 60 | 327 | 6.81 | 25.00 | 392 | 8.40 | 25.00 | 454 | 10.26 | 25.00 | 512 | 12.41 | 25.00 | 547 | 13.85 | 25.00 | 625 | 17.69 | 25.00 | 680 | 20.89 | 25.00 |
| 125 | 50 | 344 | 6.09 | 25.00 | 407 | 7.59 | 25.00 | 465 | 9.36 | 25.00 | 522 | 11.42 | 25.00 | 556 | 12.80 | 25.00 | 632 | 16.52 | 25.00 | 686 | 19.63 | 25.00 |
| 100 | 40 | 361 | 5.37 | 25.00 | 419 | 6.78 | 25.00 | 476 | 8.46 | 25.00 | 531 | 10.43 | 25.00 | 564 | 11.76 | 25.00 | 639 | 15.35 | 25.00 | 693 | 18.37 | 25.00 |
| 75 | 30 | 375 | 4.65 | 25.00 | 431 | 5.97 | 25.00 | 486 | 7.56 | 25.00 | 540 | 9.44 | 25.00 | 572 | 10.71 | 25.00 | 646 | 14.18 | 25.00 | 699 | 17.11 | 25.00 |
| 50 | 20 | 388 | 3.93 | 25.00 | 442 | 5.16 | 25.00 | 495 | 6.66 | 25.00 | 548 | 8.45 | 25.00 | 579 | 9.67 | 25.00 | 652 | 13.01 | 25.00 | 704 | 15.85 | 25.00 |
| 25 | 10 | 399 | 3.21 | 25.00 | 451 | 4.35 | 25.00 | 503 | 5.76 | 25.00 | 555 | 7.45 | 25.00 | 586 | 8.63 | 25.00 | 658 | 11.84 | 25.00 | 710 | 14.59 | 25.00 |
| 0 | 0 | 409 | 2.49 | 25.00 | 460 | 3.54 | 25.00 | 511 | 4.86 | 25.00 | 562 | 6.46 | 25.00 | 592 | 7.58 | 25.00 | 664 | 10.67 | 25.00 | 715 | 13.33 | 25.00 |

Curves refer to air at 68°F temperature and 29.92 In Hg atmospheric pressure (abs) measured at inlet port.
 Values for flow and power consumption: +/-10% tolerance.
 Data subject to change without notice.