



SCL K12-TS-MOR																							
		2000			2250			2500			2750			2900			3250			3500			
Pressure	dp [mbar]	dp [inWG]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]
	200	80	-	-	-	-	-	-	-	-	-	-	-	-	934	26.19	30.00	-	-	-	-	-	-
	175	70	-	-	-	-	-	-	-	-	-	892	21.97	30.00	963	24.23	30.00	-	-	-	-	-	-
	150	60	-	-	-	680	14.03	30.00	803	16.87	30.00	923	20.11	30.00	992	22.27	30.00	1152	27.97	30.00	-	-	-
	125	50	594	10.21	30.00	718	12.51	30.00	837	15.18	30.00	953	18.26	30.00	1022	20.31	30.00	1178	25.78	30.00	-	-	-
	100	40	636	8.85	30.00	755	10.99	30.00	871	13.49	30.00	984	16.40	30.00	1051	18.35	30.00	1205	23.58	30.00	1313	27.94	30.00
	75	30	678	7.50	30.00	793	9.47	30.00	905	11.80	30.00	1015	14.54	30.00	1080	16.39	30.00	1231	21.38	30.00	1337	25.57	30.00
	50	20	721	6.15	30.00	831	7.95	30.00	939	10.11	30.00	1046	12.68	30.00	1110	14.43	30.00	1257	19.18	30.00	1361	23.20	30.00
	25	10	763	4.80	30.00	869	6.43	30.00	973	8.42	30.00	1077	10.82	30.00	1139	12.47	30.00	1283	16.98	30.00	1386	20.84	30.00
	0	0	806	3.45	30.00	906	4.91	30.00	1007	6.73	30.00	1108	8.96	30.00	1168	10.50	30.00	1309	14.79	30.00	1410	18.47	30.00

Curves refer to air at 68°F temperature and 29.92 In Hg atmospheric pressure (abs) measured at inlet port.
 Values for flow and power consumption: +/-10% tolerance.
 Data subject to change without notice.