



SCL K12-TS-MOR																								
		2000			2250			2500			2750			2900			3250			3500				
Vacuum	dp [mbar]	dp [inWG]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	
	200	80	-	-	-	-	-	-	-	-	-	-	-	-	-	878	26.19	30.00	-	-	-	-	-	-
	175	70	-	-	-	-	-	-	-	-	-	842	21.97	30.00	921	24.23	30.00	-	-	-	-	-	-	
	150	60	-	-	-	612	14.03	30.00	754	16.87	30.00	886	20.11	30.00	962	22.27	30.00	1131	27.97	30.00	-	-	-	
	125	50	526	10.21	30.00	671	12.51	30.00	804	15.18	30.00	929	18.26	30.00	1001	20.31	30.00	1164	25.78	30.00	-	-	-	
	100	40	593	8.85	30.00	726	10.99	30.00	850	13.49	30.00	969	16.40	30.00	1038	18.35	30.00	1196	23.58	30.00	1306	27.94	30.00	
	75	30	655	7.50	30.00	777	9.47	30.00	894	11.80	30.00	1007	14.54	30.00	1073	16.39	30.00	1226	21.38	30.00	1334	25.57	30.00	
	50	20	711	6.15	30.00	824	7.95	30.00	934	10.11	30.00	1043	12.68	30.00	1107	14.43	30.00	1255	19.18	30.00	1360	23.20	30.00	
	25	10	761	4.80	30.00	867	6.43	30.00	972	8.42	30.00	1076	10.82	30.00	1138	12.47	30.00	1283	16.98	30.00	1386	20.84	30.00	
	0	0	806	3.45	30.00	906	4.91	30.00	1007	6.73	30.00	1108	8.96	30.00	1168	10.50	30.00	1309	14.79	30.00	1410	18.47	30.00	

Curves refer to air at 68°F temperature, measured at inlet port and 29.92 In Hg atmospheric backpressure (abs)  
 Values for flow and power consumption: +/-10% tolerance.  
 Data subject to change without notice.