



SCL K06-TD-MOR																						
		2000			2250			2500			2750			2900			3250			3500		
dp [mbar]	dp [inWG]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]
400	160	-	-	-	-	-	-	-	-	-	-	-	-	74	6.44	10.00	118	7.55	10.00	145	8.41	10.00
375	150	-	-	-	-	-	-	-	-	-	-	-	-	84	6.11	10.00	125	7.18	10.00	151	8.02	10.00
350	140	-	-	-	-	-	-	-	-	-	75	5.37	10.00	94	5.78	10.00	133	6.81	10.00	157	7.62	10.00
325	130	-	-	-	-	-	-	51	4.44	10.00	85	5.06	10.00	103	5.45	10.00	140	6.44	10.00	163	7.22	10.00
300	120	-	-	-	-	-	-	63	4.16	10.00	95	4.75	10.00	111	5.12	10.00	147	6.07	10.00	169	6.82	10.00
275	110	-	-	-	-	-	-	74	3.87	10.00	104	4.43	10.00	120	4.79	10.00	153	5.70	10.00	175	6.42	10.00
250	100	-	-	-	53	3.10	10.00	85	3.59	10.00	113	4.12	10.00	127	4.46	10.00	159	5.33	10.00	180	6.02	10.00
225	90	-	-	-	66	2.85	10.00	95	3.30	10.00	121	3.81	10.00	135	4.13	10.00	165	4.96	10.00	185	5.63	10.00
200	80	-	-	-	78	2.59	10.00	105	3.02	10.00	129	3.49	10.00	142	3.80	10.00	171	4.59	10.00	190	5.23	10.00
175	70	60	1.97	10.00	89	2.33	10.00	114	2.74	10.00	136	3.18	10.00	148	3.47	10.00	176	4.22	10.00	195	4.83	10.00
150	60	73	1.75	10.00	99	2.08	10.00	122	2.45	10.00	143	2.87	10.00	155	3.14	10.00	181	3.85	10.00	199	4.43	10.00
125	50	85	1.52	10.00	108	1.82	10.00	129	2.17	10.00	149	2.56	10.00	160	2.81	10.00	186	3.48	10.00	203	4.03	10.00
100	40	96	1.29	10.00	117	1.57	10.00	136	1.88	10.00	155	2.24	10.00	166	2.48	10.00	190	3.11	10.00	207	3.64	10.00
75	30	105	1.06	10.00	124	1.31	10.00	143	1.60	10.00	160	1.93	10.00	170	2.15	10.00	194	2.75	10.00	211	3.24	10.00
50	20	113	0.84	10.00	131	1.05	10.00	148	1.31	10.00	165	1.62	10.00	175	1.82	10.00	198	2.38	10.00	214	2.84	10.00
25	10	120	0.61	10.00	137	0.80	10.00	153	1.03	10.00	169	1.30	10.00	179	1.49	10.00	201	2.01	10.00	217	2.44	10.00
0	0	126	0.38	10.00	142	0.54	10.00	157	0.74	10.00	173	0.99	10.00	183	1.16	10.00	205	1.64	10.00	220	2.04	10.00

Curves refer to air at 68°F temperature, measured at inlet port and 29.92 In Hg atmospheric backpressure (abs)
 Values for flow and power consumption: +/-10% tolerance.
 Data subject to change without notice.