



Variable Speed Table
2000 rpm – 4000 rpm
VAR-e08MSV-0

		SCL e08-MS																										
		2000			2250			2500			2750			2900			3250			3500			3750			4000		
Vacuum	dp [inWG]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]	Q [cfm]	Pow [hp]	E.M. [hp]
	130	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	206	10.32	15.00	253	11.33	15.00	297	12.45	15.00
	120	-	-	-	-	-	-	-	-	-	-	-	-	140	7.58	10.00	175	8.75	10.00	224	9.65	15.00	269	10.65	15.00	311	11.74	15.00
	110	-	-	-	-	-	-	-	-	-	-	-	-	159	7.02	7.50	195	8.13	10.00	242	9.01	10.00	284	9.97	15.00	325	11.04	15.00
	100	-	-	-	-	-	-	-	-	-	-	-	-	177	6.47	7.50	215	7.52	10.00	258	8.37	10.00	299	9.31	10.00	338	10.35	15.00
	90	-	-	-	-	-	-	-	-	-	167	5.52	7.50	194	5.93	7.50	233	6.92	7.50	275	7.75	10.00	314	8.66	10.00	351	9.67	15.00
	80	-	-	-	-	-	-	140	4.41	7.50	186	5.01	7.50	212	5.40	7.50	251	6.34	7.50	290	7.14	7.50	328	8.02	10.00	364	9.00	10.00
	70	-	-	-	-	-	-	161	3.95	7.50	204	4.51	5.50	228	4.88	5.50	268	5.77	7.50	306	6.54	7.50	342	7.40	10.00	376	8.35	10.00
	60	-	-	-	138	3.02	5.50	181	3.49	5.50	221	4.02	5.50	244	4.37	5.50	284	5.22	5.50	320	5.96	7.50	355	6.79	7.50	388	7.70	10.00
	50	115	2.22	5.50	160	2.60	5.50	201	3.04	5.50	238	3.53	5.50	260	3.86	5.50	300	4.68	5.50	334	5.39	7.50	367	6.19	7.50	400	7.07	7.50
	40	141	1.84	5.50	182	2.19	5.50	219	2.60	5.50	255	3.06	5.50	275	3.36	5.50	314	4.15	5.50	347	4.83	5.50	379	5.60	7.50	411	6.45	7.50
	30	165	1.48	5.50	202	1.80	5.50	237	2.16	5.50	270	2.59	5.50	290	2.87	5.50	328	3.64	5.50	360	4.29	5.50	391	5.02	5.50	421	5.84	7.50
20	188	1.14	5.50	221	1.41	5.50	254	1.74	5.50	285	2.13	5.50	304	2.39	5.50	342	3.14	5.50	372	3.76	5.50	402	4.46	5.50	432	5.24	5.50	
10	209	0.80	5.50	239	1.04	5.50	270	1.33	5.50	300	1.68	5.50	318	1.91	5.50	354	2.66	5.50	383	3.24	5.50	413	3.90	5.50	442	4.66	5.50	
0	228	0.47	5.50	257	0.68	5.50	285	0.93	5.50	314	1.23	5.50	331	1.45	5.50	366	2.19	5.50	394	2.74	5.50	423	3.37	5.50	451	4.08	5.50	

Highlighted values represent the maximum vacuum for the installed motor power.

Curves refer to air at 68°F temperature, measured at inlet port and 29.92 In Hg atmospheric backpressure (abs) Values for flow and power consumption: +/-10% tolerance.
Data subject to change without notice.